

## YANG MING DG CARGO PROHIBITED &amp; RESTRICTED LIST

R.19

X: Prohibited / R : Restricted

IMO	UN No	PROPER SHIPPING NAME	YML
1	ALL	All Class 1, except UN0503 SAFETY DEVICES, PYROTECHNIC	X
2.1	ALL	FLAMMABLE GASES in REEFER	X
	1032	DIMETHYLAMINE, ANHYDROUS	X
	1049	HYDROGEN, COMPRESSED	X
	1057	LIGHTERS containing flammable gas or LIGHTER REFILLS containing flammable gas Disposable type with flint is prohibited. Other types which normally contain igniting device of either electronic or piezoelectric type are acceptable subject to certificates and restriction accord with below conditions: 1. Certificate complying with ISO9994 : 2018 criterion. 2. Survey Reports of pre-shipment inspection with LEL test. And, photos of lighter, packing, stowage condition while half & full loaded, reinforcement of container. 3. Warning sign at door, describing keep ignition sources away. 4. Suspend acceptance from May 15 to Sep 30. 5. Full information of (1),(2),(3) and (4) must be attached with application.	R
	1961	ETHANE, REFRIGERATED LIQUID	X
	1966	HYDROGEN, REFRIGERATED LIQUID	X
	1972	METHANE, REFRIGERATED LIQUID or NATURAL GAS, REFRIGERATED LIQUID with high methane content	X
	2203	SILANE	X
	3138	ETHYLENE, ACETYLENE AND PROPYLENE MIXTURE, REFRIGERATED LIQUID containing at least 71.5% ethylene, with not more than 22.5% acetylene and not more than 6% propylene	X
	3468	HYDROGEN IN A METAL HYDRIDE STORAGE SYSTEM or HYDROGEN IN A METAL HYDRIDE STORAGE SYSTEM CONTAINED IN EQUIPMENT or HYDROGEN IN A METAL HYDRIDE STORAGE SYSTEM PACKED WITH EQUIPMENT	X
2.2	2455	METHYL NITRITE	X
2.3	ALL	All Class 2.3	X
3	ALL	FLASH POINT (FP< 23 Degree C) in REEFER	X
	1131	CARBON DISULPHIDE	X
	1194	ETHYL NITRITE SOLUTION- Pure Ethyl Nitrite is prohibited	R
	1222	ISOPROPYL NITRATE	X
	1261	NITROMETHANE	X
	1280	PROPYLENE OXIDE - Prohibited on carriage in tank to Singapore including transit	R
	1865	n-PROPYL NITRATE	X
	3256	ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S. with flashpoint above 60 °C, at or above its flashpoint (See Note 10)	R
	3343	NITROGLYCERIN MIXTURE, DESENSITIZED, LIQUID, FLAMMABLE, N.O.S. with not more than 30% nitroglycerin, by mass (See Note 10)	R
	3357	NITROGLYCERIN MIXTURE, DESENSITIZED, LIQUID, N.O.S. with not more than 30% nitroglycerin, by mass (See Note 10)	R
3379	DESENSITIZED EXPLOSIVE, LIQUID, N.O.S. (See Note 10)	R	
	2304	NAPHTHALENE, MOLTEN	X
	2448	SULPHUR, MOLTEN	X
	2956	5-tert-BUTYL-2,4,6-TRINITRO-m-XYLENE or MUSK XYLENE	X
	3097	FLAMMABLE SOLID, OXIDIZING, N.O.S. (See Note 10 and 11)	R
	3176	FLAMMABLE SOLID, ORGANIC, MOLTEN, N.O.S.	X
	3221	SELF-REACTIVE LIQUID TYPE B	X
	3222	SELF-REACTIVE SOLID TYPE B	X
	3223	SELF-REACTIVE LIQUID TYPE C	X
	3224	SELF-REACTIVE SOLID TYPE C	X
	3225	SELF-REACTIVE LIQUID TYPE D	X
3226	SELF-REACTIVE SOLID TYPE D	X	

4.1	3227	SELF-REACTIVE LIQUID TYPE E	X	
	3228	SELF-REACTIVE SOLID TYPE E	X	
	3229	SELF-REACTIVE LIQUID TYPE F	X	
	3230	SELF-REACTIVE SOLID TYPE F	X	
	3231	SELF-REACTIVE LIQUID TYPE B, TEMPERATURE CONTROLLED	X	
	3232	SELF-REACTIVE SOLID TYPE B, TEMPERATURE CONTROLLED	X	
	3233	SELF-REACTIVE LIQUID TYPE C, TEMPERATURE CONTROLLED	X	
	3234	SELF-REACTIVE SOLID TYPE C, TEMPERATURE CONTROLLED	X	
	3235	SELF-REACTIVE LIQUID TYPE D, TEMPERATURE CONTROLLED	X	
	3236	SELF-REACTIVE SOLID TYPE D, TEMPERATURE CONTROLLED	X	
	3237	SELF-REACTIVE LIQUID TYPE E, TEMPERATURE CONTROLLED	X	
	3238	SELF-REACTIVE SOLID TYPE E, TEMPERATURE CONTROLLED	X	
	3239	SELF-REACTIVE LIQUID TYPE F, TEMPERATURE CONTROLLED	X	
	3240	SELF-REACTIVE SOLID TYPE F, TEMPERATURE CONTROLLED	X	
	3319	NITROGLYCERIN MIXTURE, DESENSITIZED, SOLID, N.O.S. with more than 2% but not more than 10% nitroglycerin, by mass (See Note 10)	R	
	3380	DESENSITIZED EXPLOSIVE, SOLID, N.O.S.	X	
	Var.	SELF-REACTIVE SUBSTANCE/BLOWING AGENT EMBARGOES ALL SELF-REACTIVE SUBSTANCES WITH SUBSIDIARY EXPLOSIVE RISKS.	X	
4.2	1361	CARBON animal or vegetable origin - (See UN1362 & Note 12 ) <For Non-DG CHARCOAL> The acceptance is only for Yang Ming booking on Yang Ming operated vessels. (See Note 12)	R	
	1362	CARBON, ACTIVATED		
		UN1361 & UN1362 originated from elsewhere other than from USA are subject to below conditions: ( The acceptance is only for Yang Ming booking on Yang Ming operated vessels ) a) Submission of Shipper's weathering report stating : 1) Good ventilation in warehouses / storage places 2) Minimum of 14 days of pre-cooling prior to packaging. b) Vanning survey certificate confirming that: 1) Cargo is packed in accordance with IMDG Code. 2) Packaging should be impervious to air and in good condition, and must not be torn. 3) Temperature of cargo should not be more than 5 degree Celsius above the ambient temperature. 4) At least 40 boxes/per ctnr will be examined for charcoal temperature. If one of them is discovered as unqualified during examination, 10 more boxes will be added for inspection. If there more than two are unqualified, the said container will be rejected. Moreover, Yang Ming local agent needs to pay a visit to monitor the survey as well. 5) The commodity moisture data shall be offered during Item (3) examination. 6) There should be no burning smell or presence of smoke during vanning. 7) Void space of 30 cm must be left on top of cargo and at door end to assist fire fighting. 8) The surveyor and Yang Ming local staff are required submitting a statement after the joint survey. c) The Shipper's weathering report for each shipper is required to be submitted only once. d) The vanning survey certificate to be submitted for every shipment (B/L lot) and every vessel/voyage and in addition to "(b)" the following details to be included: 1) total number and size of containers 2) container numbers 3) seal numbers against respective container numbers 4) date of vanning of each container		
	1364	COTTON WASTE, OILY		X
	1374	FISHMEAL, UNSTABILIZED High hazard. Unrestricted moisture content, Unrestricted fat content in excess of 12%, by mass; unrestricted fat content in excess of 15%, by mass, in the case of anti-oxidant treated fishmeal or fishscrap or FISHSCRAP, UNSTABILIZED High hazard. Unrestricted moisture content, Unrestricted fat content in excess of 12%, by mass; unrestricted fat content in excess of 15%, by mass, in the case of anti-oxidant treated fishmeal or fishscrap		X

1376	IRON OXIDE, SPENT obtained from coal gas purification or IRON SPONGE, SPENT obtained from coal gas purification- This substance should have been cooled and weathered for not less than eight weeks before shipment, unless packed in a metal drum. (See IMDG code DGL column 17)	R	
1381	PHOSPHORUS, WHITE, DRY or PHOSPHORUS, WHITE, UNDER WATER or PHOSPHORUS, WHITE, IN SOLUTION or PHOSPHORUS, <b>YELLOW</b> , DRY or PHOSPHORUS, <b>YELLOW</b> , UNDER WATER or PHOSPHORUS, <b>YELLOW</b> , IN SOLUTION	X	
1383	PYROPHORIC METAL, N.O.S. or PYROPHORIC ALLOY, N.O.S.	X	
1384	SODIUM DITHIONITE or SODIUM HYDROSULPHITE	X	
1386	than 10% oil or more than 20% oil and moisture combined or SEED CAKE containing vegetable oil (b) solvent extractions and expelled seeds, containing not more than 10% of oil and when the amount of moisture is higher than 10%, not more than 20% of oil and moisture combined	X	
1387	WOOL WASTE, WET	X	
1857	TEXTILE WASTE, WET	X	
2217	SEED CAKE with not more than 1.5% oil and not more than 11% moisture	X	
2447	PHOSPHORUS, WHITE, MOLTEN	X	
2845	PYROPHORIC LIQUID, ORGANIC, N.O.S.	X	
2846	PYROPHORIC SOLID, ORGANIC N.O.S.	X	
2870	ALUMINIUM BOROXYDRIDE or ALUMINIUM BOROXYDRIDE IN DEVICES	X	
2881	METAL CATALYST, DRY	X	
3127	SELF-HEATING SOLID, OXIDIZING, N.O.S. (See Note 10 and 11)	R	
3194	PYROPHORIC LIQUID, INORGANIC, N.O.S.	X	
3200	PYROPHORIC SOLID, INORGANIC, N.O.S.	X	
3255	tert-BUTYL HYPOCHLORITE (See Note 10 and 11)	R	
3341	THIOUREA DIOXIDE	X	
3391	ORGANOMETALLIC SUBSTANCE, SOLID, PYROPHORIC	X	
3392	ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC	X	
3393	ORGANOMETALLIC SUBSTANCE, SOLID, PYROPHORIC, WATER-REACTIVE	X	
3394	ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE	X	
Var.	SUBSTANCES WHICH IGNITE ON EXPOSURE TO AIR	X	
4.3	1395	ALUMINIUM FERROSILICON POWDER	X
	1398	ALUMINIUM SILICON POWDER, UNCOATED	X
	1405	CALCIUM SILICIDE -Requires a certificate from the maker or shipper, stating that the shipment was stored under cover, but in the open air, in the size in which it was packaged, for not less than 3 days prior to shipment. (See IMDG special provision 932)	R
	1408	FERROSILICON with 30% or more but less than 90% silicon-Requires a certificate from the maker or shipper, stating that the shipment was stored under cover, but in the open air, in the size in which it was packaged, for not less than 3 days prior to shipment. (See IMDG special provision 932)	R
	1409	METAL HYDRIDES, WATER-REACTIVE, N.O.S.	X
	1415	LITHIUM	X
	1418	MAGNESIUM POWDER or MAGNESIUM ALLOYS POWDER	X
	1928	METHYLMAGNESIUM BROMIDE IN ETHYL ETHER	X
	3133	WATER-REACTIVE SOLID, OXIDIZING, N.O.S. (See Note 10 and 11)	R
1479	OXIDIZING SOLID, N.O.S. If the technical name is Calcium Hypochlorite, it is prohibited.	R	
1512	ZINC AMMONIUM NITRITE	X	
1748	CALCIUM HYPOCHLORITE, DRY with more than 39% available chlorine (8.8% available oxygen) or CALCIUM HYPOCHLORITE MIXTURE, DRY with more than 39% available chlorine (8.8% available oxygen)	X	
1942	AMMONIUM NITRATE with not more than 0.2% combustible substances, including any organic substance calculated as carbon, to the exclusion of any other added substance (See Note 9)	R	

5.1	2014	HYDROGEN PEROXIDE, AQUEOUS SOLUTION with not less than 20% but not more than 60% hydrogen peroxide (stabilized as necessary) - <b>ONLY ACCEPT IN TANK CONTAINER</b>	R
	2015	HYDROGEN PEROXIDE, STABILIZED with more than 60% hydrogen peroxide or HYDROGEN PEROXIDE, AQUEOUS SOLUTION, STABILIZED with more than 60% hydrogen peroxide - Prohibited at Hong Kong on both import and transit <b>- ONLY ACCEPT IN TANK CONTAINER</b>	R
	2067	AMMONIUM NITRATE BASED FERTILIZER (See Note 9)	R
	2208	CALCIUM HYPOCHLORITE MIXTURE, DRY with more than 10% but not more than 39% available chlorine	X
	2426	AMMONIUM NITRATE, LIQUID (hot concentrated solution)	X
	2468	TRICHLOROISOCYANURIC ACID, DRY - Cargo exported from Asia region is prohibited.	R
	2880	CALCIUM HYPOCHLORITE, HYDRATED with not less than 5.5% but not more than 16% water or CALCIUM HYPOCHLORITE, HYDRATED MIXTURE with not less than 5.5% but not more than 16% water	X
	3100	OXIDIZING SOLID, SELF-HEATING, N.O.S. (See Note 10 and 11)	R
	3121	OXIDIZING SOLID, WATER-REACTIVE, N.O.S. (See Note 10 and 11)	R
	3137	OXIDIZING SOLID, FLAMMABLE, N.O.S. (See Note 10 and 11)	R
	3149	HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED - <b>ONLY ACCEPT IN TANK CONTAINER</b>	R
	3212	HYPOCHLORITES, INORGANIC N.O.S.	X
	3375	AMMONIUM NITRATE EMULSION intermediate for blasting explosives or AMMONIUM NITRATE SUSPENSION intermediate for blasting explosives or AMMONIUM NITRATE GEL intermediate for blasting explosives -Competent authority approval is required.(See General Stowage Requirements)	R
	3485	CALCIUM HYPOCHLORITE, DRY, CORROSIVE with more than 39% available chlorine (8.8% available oxygen) or CALCIUM HYPOCHLORITE MIXTURE, DRY, CORROSIVE with more than 39% available chlorine (8.8% available oxygen)	X
	3486	CALCIUM HYPOCHLORITE MIXTURE, DRY, CORROSIVE with more than 10% but not more than 39% available chlorine	X
	3487	CALCIUM HYPOCHLORITE, HYDRATED, CORROSIVE with not less than 5.5% but not more than 16% water or CALCIUM HYPOCHLORITE, HYDRATED MIXTURE, CORROSIVE with not less than 5.5% but not more than 16% water	X
	5.2	3101	ORGANIC PEROXIDE TYPE B, LIQUID
3102		ORGANIC PEROXIDE TYPE B, SOLID	X
3111		ORGANIC PEROXIDE TYPE B, LIQUID, TEMPERATURE CONTROLLED	X
3112		ORGANIC PEROXIDE TYPE B, SOLID, TEMPERATURE CONTROLLED	X
3113		ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE CONTROLLED	X
3114		ORGANIC PEROXIDE TYPE C, SOLID, TEMPERATURE CONTROLLED	X
3115		ORGANIC PEROXIDE TYPE D, LIQUID, TEMPERATURE CONTROLLED	X
3116		ORGANIC PEROXIDE TYPE D, SOLID, TEMPERATURE CONTROLLED	X
3117		ORGANIC PEROXIDE TYPE E, LIQUID, TEMPERATURE CONTROLLED	X
3118		ORGANIC PEROXIDE TYPE E, SOLID, TEMPERATURE CONTROLLED	X
3119		ORGANIC PEROXIDE TYPE F, LIQUID, TEMPERATURE CONTROLLED	X
3120		ORGANIC PEROXIDE TYPE F, SOLID, TEMPERATURE CONTROLLED	X
VAR	1. EMBARGOES ALL OTHER ORGANIC PEROXIDES WITH SUBSIDIARY EXPLOSIVE RISKS. 2. SADT( SELF-ACCELERATING DECOMPOSITION TEMPERATURE) BELOW 60 DEGREE C IS PROHIBITED.	X	
	1135	ETHYLENE CHLOROHYDRIN	X
	1510	TETRANITROMETHANE (See Note 8)	R
	1600	DINITROTOLUENES, MOLTEN	X
	1614	HYDROGEN CYANIDE, STABILIZED containing less than 3% water and absorbed in a porous inert material (See Note 10)	R
	1649	MOTOR FUEL ANTI-KNOCK MIXTURE	X

6.1	3483	<b>MOTOR FUEL ANTI-KNOCK MIXTURE, FLAMMABLE</b>	X	
	2023	EPICHLOROHYDRIN (See Note 8)	R	
	2249	DICHLORODIMETHYL ETHER, SYMMETRICAL (See Note 10 and 11)	R	
	2312	PHENOL, MOLTEN	X	
	2480	METHYL ISOCYANATE (See Note 8)	R	
	3123	TOXIC LIQUID, WATER-REACTIVE, N.O.S. (For PG I - See Note 10; for PG II - no restriction)	R	
	3125	TOXIC SOLID, WATER-REACTIVE, N.O.S. (For PG I - See Note 10; for PG II - no restriction)	R	
	3250	CHLOROACETIC ACID, MOLTEN	X	
	3315	CHEMICAL SAMPLE, TOXIC (See Note 10)	R	
	3507	URANIUM HEXAFLUORIDE, RADIOACTIVE MATERIAL, EXCEPTED PACKAGE less than 0.1 kg per package, non-fissile or fissile-excepted	X	
6.2	ALL	All Class 6.2	X	
7	ALL	All Class 7	X	
8	1744	BROMINE or BROMINE SOLUTION (See Note 8)	R	
9	2211	<b>POLYMERIC BEADS, EXPANDABLE evolving flammable vapour</b> R1: Only accept in open-top container R2: When in closed container, IMDG code special provision 965 point 2 shall be met R3: Stow on deck only R4: Addition warning mark "CAUTION-MAY CONTAIN FLAMMABLE VAPOUR" required on container door	R	
		2212	<b>ASBESTOS, AMPHIBOLE (amosite, tremolite, actinolite, anthophyllite, crocidolite)</b>	X
		2315	<b>POLYCHLORINATED BIPHENYLS, LIQUID</b>	X
		2590	<b>ASBESTOS, CHRYSOTILE</b>	X
	3090	<b>LITHIUM METAL BATTERIES (including lithium alloy batteries) - Include Non-DG (See Note 12)</b>	R	
	3091	<b>LITHIUM METAL BATTERIES CONTAINED IN EQUIPMENT (including lithium alloy batteries) or LITHIUM METAL BATTERIES PACKED WITH EQUIPMENT (including lithium alloy batteries) - Include Non-DG (See Note 12)</b>	R	
	3151	<b>POLYHALOGENATED BIPHENYLS, LIQUID or POLYHALOGENATED TERPHENYLS, LIQUID</b>	X	
	3152	<b>POLYHALOGENATED BIPHENYLS, SOLID or POLYHALOGENATED TERPHENYLS, SOLID</b>	X	
	3245	<b>GENETICALLY MODIFIED MICROORGANISMS or GENETICALLY MODIFIED ORGANISMS</b>	X	
	3257	<b>ELEVATED TEMPERATURE LIQUID, N.O.S. at or above 100°C and below its flashpoint (including molten metals, molten salts, etc.) (See Note 10)</b>	R	
	3258	<b>ELEVATED TEMPERATURE SOLID, N.O.S. at or above 240°C (See Note 10)</b>	R	
	3314	<b>PLASTICS MOULDING COMPOUND in dough, sheet or extruded rope form, evolving flammable vapour</b> R1: Only accept in open-top container or one- door- off container R2: When in closed container, IMDG code special provision 965 point 2 shall be met R3: Stow on deck only R4: Addition warning mark "CAUTION-MAY CONTAIN FLAMMABLE VAPOUR" required on container door	R	
		3432	<b>POLYCHLORINATED BIPHENYLS, SOLID</b>	X
		3480	<b>LITHIUM METAL BATTERIES - Include Non-DG (See Note 12)</b>	R
3481		<b>LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT or LITHIUM ION BATTERIES PACKED WITH EQUIPMENT - Include Non-DG (See Note 12)</b>	R	

	<p><b>1. DANGEROUS GOODS IN REEFER SUBJECT TO FOLLOWING CONDITIONS:</b></p> <p>a. only accept Class 2.2, 3 (Flash Point ≥ 23 Degree C), 4.1, 4.2, 4.3, 5.1, 8 and 9 (except UN2211&amp;</p> <p>b. which are without subsidiary label 1, 3 (Flash Point &lt; 23 Degree C), 6.1</p> <p>c. quality control purpose only</p> <p>d. SDS ( safety data sheet) to be offered upon application.</p>	R
	<b>2. GOODS REQUIRING TEMPERATURE CONTROL BY IMDG CODE</b>	X
	<b>3. DANGEROUS GOODS IN CONTAINER AS BULK</b>	X
	<b>4. WASTE</b>	X
	<b>5. ISO TANK SHIPMENTS NOT ACCEPTABLE FOR HONG KONG MID-STREAM HANDLING</b>	X
	<p><b>6. DANGEROUS GOODS IN SOLID WITH THE MELTING POINT BELOW 60 DEGREE C WILL NOT BE ACCEPTABLE WHEN THEY PACKED IN BELOW PACKAGING TYPE.</b></p> <p><b>Packagings</b></p> <p><b>Drums:1D and 1G</b></p> <p><b>Boxes:4C1, 4C2, 4D, 4F, 4G and 4H1</b></p> <p><b>Bags: 5L1, 5L2, 5L3, 5H1, 5H2, 5H3, 5H4, 5M1 and 5M2</b></p> <p><b>Composite:6HC, 6HD2, 6HG1, 6HG2, 6HD1, 6PC, 6PD1, 6PD2, 6PG1, 6PG2 and 6PH1</b></p> <p><b>Large packagings</b></p> <p><b>Flexible plastics:51H (outer packaging)</b></p> <p><b>IBCs</b></p> <p><b>For substances of packing group I:</b></p> <p><b>All types of IBCs</b></p> <p><b>For substances of packing groups II and III:</b></p> <p><b>Wooden:11C, 11D and 11F</b></p> <p><b>Fibreboard:11G</b></p> <p><b>Flexible:13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 and 13M2</b></p> <p><b>Composite:11HZ2 and 21HZ2.</b></p> <p><b>(According to IMDG Code 4.1.3.4, these packagings shall not be used when the substances being transported may become liquid during transport.)</b></p>	X
	<p><b>7.SPECIAL PROVISION 349/350/351/352/353/900: THE TRANSPORT OF THE FOLLOWING SUBSTANCES IS PROHIBITED</b></p> <p>AMMONIUM BROMATE</p> <p>AMMONIUM BROMATE, SOLUTION</p> <p>AMMONIUM CHLORATE</p> <p>AMMONIUM CHLORATE, SOLUTION</p> <p>AMMONIUM CHLORITE</p> <p>AMMONIUM CHLORITE, SOLUTION</p> <p>AMMONIUM HYPOCHLORATE</p> <p>AMMONIUM NITRATE liable to self-heating sufficient to initiate a decomposition</p> <p>AMMONIUM NITRITES and mixtures of an inorganic nitrite with an ammonium salt</p> <p>AMMONIUM PERMANGANATE</p> <p>AMMONIUM PERMANGANATE, SOLUTION</p> <p>CHLORIC ACID AQUEOUS SOLUTION with more than 10% chloric acid</p> <p>ETHYL NITRITE pure</p> <p>HYDROCYANIC ACID, AQUEOUS SOLUTION (HYDROGEN CYANIDE, AQUEOUS SOLUTION) with more than 20% hydrogen cyanide</p>	X

Note